

# BATTERY TERMINALS



**Top Stud Battery Terminals**  
(Crimp Type Battery Rings)

100% Pure Copper w/Tin Plating • Fully Annealed  
A single, double or 3-way connection can be made by stacking parts.

UNIT PACKAGE: 5

Auveco Part No.	Cable Size	Length	Stud Size
12770	1/0 Ga.	2"	3/8"
14465	3/0 Ga.	2"	3/8"
14466	■4/0 Ga. .559 I.D.	2-1/4"	3/8"

■For Rope Stranded 4/0 Cable (most common construction)



**Copper Battery Cable Lugs**

Auveco Part No.	Cable Size	Stud Size	Unit Pkg.
5794	4 Ga.	3/8"	25
5796	1/0 Ga.	3/8"	25
11467	2/0 Ga.	1/2"	10

Use Auveco No. 7996 or No. 7997 Crimping Tool



**Butt Connector (Double Flared)**

Pure Copper with Tin Plating

Applications: Field or shop splicing of battery cables and welding cables.

Auveco Part No.	Cable Size	Length	Unit Pkg.
11727	1 Ga.	1-3/8"	5
11728	1/0 Ga.	1-1/2"	5
11729	2/0 Ga.	1-3/4"	5
11731	4/0 Ga.	1-7/8"	2

Use Auveco Crimping Tool No. 7997



**Brass Side Terminal Battery Bolt & Connector**

**15184**

3/8-16 Thread  
Overall Length:  
1-1/4"

UNIT PACKAGE: 1



**Zinc Plated Battery Side Terminal Bolt**

**11083**  
(8917444)

Thread Size 3/8-16  
Overall Length:  
1-1/8"  
GM


UNIT PACKAGE: 10



**19199**  
(12004188)  
Zinc

Battery Side Terminal Bolt  
Thread Size: 3/8"-16  
Overall Length: 1-3/4"  
GM

UNIT PACKAGE: 5



**Battery Terminal Bolt & Nut**

Zinc Chromate

Auveco Part No.	Size	Unit Pkg.
3186	5/16"-18 x 1-1/4" Bolt W/Collared Nut	100
8003	5/16"-18 x 1-1/4" Bolt W/Hex Nut	50
8870	5/16"-18 x 1-1/2" Bolt W/Collared Nut	100
14974	5/16"-18 x 1-1/4" Bolt Only	50
14975	5/16"-18 Collared Nut Only	50