



Metric Hex Socket Head Cap Screws

DIN 912

Regular Pitch - Grade 12.9

Heat Treated Alloy Steel • Plain Finish

Tensile Strength: 177,000 PSI

Auveco Part No.		Diameter & Pitch	Length
Unit Package			
10	100		
10845	10872	4mm-.7	12mm
10846	10873	5mm-.8	12mm
10847	5mm-.8	16mm
10848	10875	5mm-.8	20mm
10851	10878	6mm-1.00	16mm
10853	6mm-1.00	25mm
10854	6mm-1.00	30mm
10855	8mm-1.25	16mm
10858	10885	8mm-1.25	30mm
10859	8mm-1.25	35mm
10860	8mm-1.25	40mm
10861	10mm-1.50	20mm
10862	10mm-1.50	25mm
10863	10mm-1.50	30mm
10864	10mm-1.50	40mm
10865	10mm-1.50	50mm
10866	12mm-1.75	30mm
10867	12mm-1.75	35mm
10868	12mm-1.75	40mm
10870	12mm-1.75	60mm



Metric Low Socket Head Cap Screws

DIN 6912

Regular Pitch - Grade 8.8

Heat Treated Alloy Steel • Plain Finish

Tensile Strength: 116,000 PSI

Auveco Part No.	Unit Pkg.	Diameter & Pitch	Length
10898	10	5mm-.8	10mm
10908	10	8mm-1.25	20mm

All items available in bulk.

Please Order
In Unit Package Quantities
Not Number Of Pieces



Metric Flat Head Socket Cap Screws

DIN 7991

Regular Pitch - Grade 10.9

Heat Treated Alloy Steel • Plain Finish • Tensile Strength: 150,800 PSI

Auveco Part No.		Diameter & Pitch	Length
Unit Package			
10	100		
10960	10961	6mm-1.00	16mm

Auveco Part No.	Unit Package	Diameter & Pitch	Length
10970	10	8mm-1.25	20mm
10972	10	8mm-1.25	25mm